coverguard®

TECHNICAL DATASHEET EUROWELD 2540

Ref. MO2540

Specialties





Welding







The +

High flexibility Comfort Dexterity Antistatic

PURCHASE PACKAGING

Ret.	Size	Inner	Carton
2539	9	10	120
2540	10	10	120

SALES PACKAGING

>1

Multiple

DESCRIPTION

Full grain leather lambskin Keystone thumb Safety cuff in split leather, length 15cm

SECTORS

Energy (production and distribution)

Maintenance

Construction - finishing work

Services and distribution

APPLICATIONS

Welding Argon type, metallurgy, cold welding;

Protection against contact heat up to 250°C for 15 seconds.

TECHNICAL FEATURES

Color Grey Cuff length - mm 150

ShapeGloveGloves environmentHigh heatGlove typeCut and sewn

Support material Full grain lambskin, split sowhide

for cuff

Glove construction Welding
Palm material Leather
Type of palm leather Cowhide
Finition palm leather Grain leather
Back material Leather
Type of back leather Cowhide
Finition back leather Grain leather

Type Of Cuff Safety cuff / Straight cut

Glove thickness - mm 0.7 - 0.8mm

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/12284-01/E00-no

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016



Protection from mechanical risks

EN407:2004



Protection from heat and fire

EN12477:2001+A1:2005

TYPE B

Protective gloves for welders

RETAILER STAMP

MAJ 24/02/2022