coverguard®

TECHNICAL DATASHEET EUROSTRONG 3815

Ref. MO3815

General & Heavy Duty Works





Synthetic







The +

Crinkled latex for extra grip Long cuff: increased protection Comfort

PURCHASE PACKAGING

Ref.	Size	Sachet	Carton
3813	8		60
3814	9		60
3815	10	10	60

SALES PACKAGING

Multiple

DESCRIPTION

Cut and sewn jersey cotton support, Fully coated with green latex, crinkled finish, Scalloped cuff, total length 32cm

SECTORS

Mining

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

APPLICATIONS

Market gardening, horticulture, oyster farming, fishing, handling slippery objects.

TECHNICAL FEATURES

ColorGreenShapeGlove

Gloves environment Wet environment

Glove type Dipping
Support material COTTON
Coating level Whole glove
Material of coating Latex
Tempered glove structure Supported
Support finition Crepe

Type Of Cuff Safety cuff / Scallop cut

Length - mm 320 Cuff length - mm 100

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/11/17/1784

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

((

EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016

3.1.3.1.X

Protection from mechanical risks

RETAILER STAMP

MAJ 04/06/2021