# coverguard®

# TECHNICAL DATASHEET

**KEVLAR** 

Ref. MO3890

## Cut - General & Heavy Duty Work





**Dry Environment** 

# The +

Good dexterity Long service life

#### PURCHASE PACKAGING

Réf.	Taille	Sachet	Carton
3888	8	12	144
3889	9		
3890	10	12	144

#### SALES PACKAGING

>1

Multiple

#### **DESCRIPTION**

Cut-resistant glove offers increased cut protection with Kevlar branded fiber knit. Its palmar nitrile coating ensures an optimal durability and good dexterity. Ideal for general handling of objects and materials and for maintenance. Recommended in a dry environment (or slightly oily).

Seamless knit with Kevlar brand fiber. Grey nitrile palm coating. Gauge 10.

#### **SECTORS**

#### Regional/public authorities

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

#### **APPLICATIONS**

Ggripping cables, cutting objects, handling raw materials, abrasives, tiles, ceramics, sheet metal, industrial maintenance.

### **TECHNICAL FEATURES**

群 Gauge 10

Shape Glove

**Environment** Dry, slightly oily environment

Glove type Seamless knitting

Support material Kevlar® brand fiber seamless knit

Coating level 3/4

Material of coating nitrile

Coating finition Smooth

Type Of Cuff Elastic wrist

### STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate **GB 13/89334**Delivered by SGS United Kingdom Limited (0120) Rossmore Business Park Ellesmere Port Cheshire CH65 3EN United Kingdom

 $\epsilon$ 

EPI CAT. II

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016

1443

Protection from mechanical risks

RETAILER STAMP

MAJ 17/02/2021