


Ref. 6PHP200

Non Vented Helmet General Use



The +

PERFORMANCE

- High resistance level (lateral deformation(LD), molten metal splashes (MM), low temperature - 30°C)
- ABS Shell
- CLASS 0: electrical insulation for use on low voltage installations up to 1000V a.c and 1500V d.c

COMFORT

- Integrated safety glasses
- Good fitting and lightweight feeling (head balance)
- Easy adjustment by ratchet
- Wide field of vision thanks to the short peak
- 3D textile sweatband

LIGHTWEIGHT

- 450g

Compatible with badge holder (6POBA) and earcups (6MX3000NSI)

DESCRIPTION

PHOENIX PRO Safety helmet. ABS shell, 6 points suspension harness in polyethylene with 6 textile webbing, size adjustment by ratchet from 52 to 63cm, short peak, integrated safety glasses with anti-scratch K standard and anti-fog N standard, side euro slot adapters, 3D textile sweatband, 4 point chinstrap as a standard

SECTORS

- Heavy & process industries
- Mechanicals constructions
- Light Industries
- Regional/public authorities
- Infrastructure, building industry

APPLICATIONS

Construction site, building and public works, industry...

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6PHP200NSI	-		16

SALES PACKAGING



TECHNICAL FEATURES

Shape	Safety helmet	Value electric isolation	1000V a.c / 1500V d.c
Weight	450g	Shell material	ABS
Lens marking	3-1.2 1 B	Color	Blue
Shade	Clear	Color 2	Black
Harness features	6 points harness made of polyethelene 6 textile webbings	Features	ABS Shell LDPE 6 points harness Size adjustment from 52 to 63 cm Class 0: electrical insulation up 1000V a.c and 1500V d.c
Main risk	Prevention from falling objects and head injuries or head trauma	Service life	Manufacturing date indicated under the peak Shelf life: Storage for 2 years in standard conditions Use for 5 years in good conditions
		Adjustment	Adjustment by ratchet from 52 to 63 cm

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate DPI/0497/2313

Delivered by CSI (0497) Cascina Traversagna- 21 20030 Senago (MI) Italy



EPI CAT. III

EN166:2001

Specifications (optical quality, resistance to usual risks, mechanical risks, resistance to impacts)

EN397:2012 + A1:2012

Industrial safety helmets

EN50365:2002

Electrically insulating helmets for use on low voltage installations (used for working on or near live parts of installations not exceeding 1,000 V AC or 1,500 V DC)

COVERPERF - Skincare



Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.

RETAILER STAMP

MAJ 26/05/2023